



FILTER BAGS

WATER ABSORBENT FILTER BAGS



Water Absorbent Matrix Bags

PRODUCT CATEGORIES

- **SEM** - Water Absorbent Matrix Bags

SEM Matrix Series use a new type of specially formulated and highly effective water absorbent. In its pure form, such absorbent is capable of absorbing water from oil up to 100 times of its own dry weight. However in its pure form, such water absorbent tends to be unstable. Once exposed, it quickly absorbs moisture from open air. To stabilize the water absorbent for commercial applications, we mix certain percentage of Polyester fiber into the water absorbent to formulate our unique SEM Matrix media, which is capable of absorbing and retaining water content up to 70 times of its own dry weight.

In addition to a standard line of SEM Matrix bags, we will launch SEM Designer filters simultaneously. Customers are encouraged to contact us with application specifications. As usual, we will custom make Designer SEM filters that are tailored to meet each individual customers' application requirements.

FEATURES

- Superior water absorbing capability: Absorb and retain water up to 70 times of its own dry weight.
- Dual purpose: Not only remove water from oil, but also retain contaminants of 1, 5, 10, 25 and 50 micron.
- FDA compliant none-woven felt. 100% free of silicon contamination.
- Single & multiple layer depth media composites.
- 1 ~ 50 micron range, nominal rating.
- Patented SDS™ & STS pressure seal rings, steel snap-fit rings.
- Broad chemical compatibilities.
- Fiber migration & extractable free media treatment.
- Large contaminant retention capacities, extended service lives.
- Change-out pressure differential 0.10 MPa, Max. 0.16 MPa.

TYPICAL APPLICATIONS

Quick water removal from various types of mineral oil and greases, such as hydraulic oil, lubrication oil, transformer oil, etc.

TECHNICAL SPECIFICATIONS

Filter Size	Material Availability	Material Classification	Seam Treatment	Length (mm)	Diameter (mm)	Filter Area (m²)	Volume (Liter)	Housing Used
Size 1	Water Absorbent	Felt	Welded	420	180	0.25	8.00	HEXB23, HECB23
Size 2	Water Absorbent	Felt	Welded	820	180	0.5	17.50	HEXB45, HSTB45+
Size 3	Water Absorbent	Felt	Welded	230	100	0.09	1.50	HEXB6, HECB6
Size 4	Water Absorbent	Felt	Welded	380	100	0.15	2.50	HEXB10, HECB10
Size 5	Water Absorbent	Felt	Welded	510	150	0.25	8.00	HPPB23V, HSSB23

**ISO9001 Certified
 Manufacturer**

**CORPORATE HEADQUARTERS
 Sun-Central Company, LLC.**

5644 Garland Lane, Milwaukee, Wisconsin 53129, USA.
 Telephone: 414-423-5820 Fax: 414-423-5821

E-mail: info@sccindustry.com Website: www.sccindustry.com